# ANR 19" Server Room in Cabinet

#### Active noise reduction technology in a 19" server rack

Server room in a Cabinet is a soundproof rack-mount cabinet providing up to 30 dB(A) noise reduction with up to 6 kW of heat dissipation. When combined with unique, high quality acoustic materials, the ANR acoustic 19" rack achieves previously unattainable spatial noise reduction over the entire frequency bandwidth of audible spectrum.



#### **ANR 19" Models**

ANR 19" acoustic 60110 15U

dimensions: (WxDxH) 600x1100x1265mm

ANR 19" acoustic 60110 33U

dimensions: (WxDxH) 600x1100x2065mm

ANR 19" acoustic 80120 39U

extra width and space for IT equipment dimensions: (WxDxH) 800x1200x2065mm

#### **Benefits and Features**

Gain the competitive edge - Offer noise free products


Improve productivity - Employees work better due to a quieter, less stressful environment

Eliminates noise pollution and consumes less energy Instant ROI-ANR acoustic eliminates the need for a dedicated server room

Extends the life of your equipment - constant temperature prevents server burnout

74		74
72		72
70	Server noise in conventional rack	70
68 —		68
66		66
64		64
62		62
60	Normal speech	60
58 —	Normal speech	-58
56		56
54		54
52		52
50 —	Server noise in ANR 19" acoustic rack	<b>5</b> 0
48		48
46	Average background office noise	46
44		44
42		42

#### Noise and anti-noise



Noise means any unwanted sound detected by the human ears. Noise, i.e. sound waves can be deconstructed by opposite waves with Active Noise Reduction Set.



## ANR 19" Server Room in Cabinet



#### **Mobility**

Four extra duty swivel casters with 360-degree rotation and fixing levelling feet

#### Floor space requirements

Cabinets are designed to pass through standard door openings with min. 207 cm in height. 300 mm top clearance is essential for normal operation

**Ventilation system with active noise reduction** 

Set of active silencer fan trays have up to 6 kW of total thermal load

#### **Noise reduction**

Up to 30dB(A) broadband noise reduction measured 1 m in front of enclosure

#### **Power consumption**


4x PSU 4A at 24V (approx 380 Watts)

#### Warranty

2 year warranty

Efficient ventilation system with active noise reduction, bottom cold air intake and hot air exhaust at the top





Active and passive noise reduction with high quality 3-layer acoustic foam and active noise reduction ventilation system

### **ANR 19" Models**

ANR 19" acoustic 60110 15U

Dimensions: 600x1100x1265 mm Physical capacity: 15U rack spaces Integrated PDU: 16x C13 sockets

Weight: 220 kgs

ANR 19" acoustic 60110 33U

Dimensions: 600x1100x2065 mm Physical capacity: 33U rack spaces Integrated PDU: 16x C13 sockets

Weight: 310 kgs

ANR 19" acoustic 80120 39U

Dimensions: 800x1200x2065 mm Physical capacity: 33+6U rack spaces Integrated PDU: 16x C13 sockets

Weight: 390 kgs



ANR 19" acoustic 80120 with 6 x 1U extra space on sides with vertical cable management



ANR 19" acoustic 60110 with built-in active silence fan trays

